

NATURAL RUBBER INSERTION SHEET

FEATURES

This product is made of SBR rubber with a strong polyester liner, giving it a better tear strength than ordinary rubber sheeting. Insertion rubber sheet is used for applications including gaskets, lining of toolboxes and work bench tops. This product is also available as a Natural Rubber Insertion Strip and Natural Rubber Insertion self adhesive.



PROPERTIES		RESISTANCE	
Colour	Black	UV Rating	Poor
% Of Polymer	100%	Weathering	Fair
SG (Specific Gravity)	1.6	Tear Resistance	Very Good
Tensile Strength (Mpa)	3.0	Oil & Petroleum Products	Poor
Hardness (Shore A)	65 +/-5	Acids	Poor
Elongation	200	Acids (Diluted)	Fair
Temperature Range	-20 ° C to 70 ° C	Water Swell Resistance	Very Good



Code	Description	Size (mm)	Colour	Type	Weight (kg) / LM
SRCNATINS1.5	Natural Rubber Insertion 2 ply Cotton	1.5 x 1200	Black	100% Polymer	2.80
SRCNATINS1.8	Natural Rubber Insertion 2 ply Cotton	1.8 x 1200	Black	100% Polymer	3.35
SRCNATINS3	Natural Rubber Insertion 2 ply Cotton	3 x 1200	Black	100% Polymer	5.60
SRCNATINS4.5	Natural Rubber Insertion 2 ply Cotton	4.5 x 1200	Black	100% Polymer	8.40
SRCNATINS6	Natural Rubber Insertion 2 ply Cotton	6 x 1200	Black	100% Polymer	11.20
SRCNATINS9.5	Natural Rubber Insertion 2 ply Cotton	9.5 x 1200	Black	100% Polymer	16.70

FOR ENQUIRIES:

Call us on: 1300 767 567

Western Australia Store: 102 Briggs Street Welshpool WA 6106

Queensland Store: 2/17 Alexandra Place Murarrie QLD 4172

Email: websales@indrub.com.au

Web: www.indrub.com.au



I.R.S.

**RUBBER
HARDWARE
TAPES
SEALANTS**