

# NATURAL RUBBER INSERTION STRIP

## FEATURES

This product is made of SBR rubber with a strong polyester liner, giving it a better tear strength than ordinary rubber strip. Insertion rubber strip is used in applications such as barriers and edging. This product is also available as a Natural "Insertion Sheet."



PROPERTIES		RESISTANCE	
Colour	Black	UV Rating	Poor
% Of Polymer	100%	Weathering	Fair
SG (Specific Gravity)	1.6	Tear Resistance	Very Good
Tensile Strength (Mpa)	3.0	Oil & Petroleum Products	Poor
Hardness (Shore A)	65 +/-5	Acids	Poor
Elongation	200	Acids (Diluted)	Fair
Temperature Range	-20 °C to 70 °C	Water Swell Resistance	Very Good



Code	Description	Size (mm)	Colour	Type
SRSTRIP1.5	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer
SRSTRIP1.8	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer
SRSTRIP3	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer
SRSTRIP4.5	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer
SRSTRIP6	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer
SRSTRIP9.5	Strip Rubber Insertion	25, 50, 75, 100, 150, 200, 250, 300	Black	100% Polymer

## FOR ENQUIRIES:

Call us on: 1300 767 567

Western Australia Store: 102 Briggs Street Welshpool WA 6106

Queensland Store: 2/17 Alexandra Place Murarrie QLD 4172

Email: [websales@indrub.com.au](mailto:websales@indrub.com.au)

Web: [www.indrub.com.au](http://www.indrub.com.au)



# I.R.S.

**RUBBER  
HARDWARE  
TAPES  
SEALANTS**