

Technical drawing of a 20x20mm extruded aluminum profile. The drawing includes a side view with dimensions: 600±3mm total length, 257mm distance between mounting holes, 416mm distance between mounting holes, 480mm distance between mounting holes, 585mm distance between mounting holes, 558mm distance between mounting holes, 205mm distance between mounting holes, 120mm distance between mounting holes, 18mm distance between mounting holes, 32mm distance between mounting holes, 36.2mm distance between mounting holes, 192mm distance between mounting holes, 35mm distance between mounting holes, 12mm distance between mounting holes, 1.0±0.1mm distance between mounting holes, 5.5±0.1mm distance between mounting holes, 6±0.1mm distance between mounting holes, 20X20mm profile size, 600±3mm total length, 257mm distance between mounting holes, 416mm distance between mounting holes, 480mm distance between mounting holes, 585mm distance between mounting holes, 558mm distance between mounting holes, 205mm distance between mounting holes, 120mm distance between mounting holes, 18mm distance between mounting holes, 32mm distance between mounting holes, 36.2mm distance between mounting holes, 192mm distance between mounting holes, 35mm distance between mounting holes, 12mm distance between mounting holes, 1.0±0.1mm distance between mounting holes, 5.5±0.1mm distance between mounting holes, 6±0.1mm distance between mounting holes.

Dimensions and features shown:

- Overall length: 600±3mm
- Distance between mounting holes: 257mm, 416mm, 480mm, 585mm, 558mm, 205mm, 120mm, 18mm, 32mm, 36.2mm, 192mm, 35mm, 12mm, 1.0±0.1mm, 5.5±0.1mm, 6±0.1mm
- Profile size: 20X20mm
- Mounting holes: Ø5.1, Ø7.5, Ø4.2, Ø6.5, Ø5.2
- End view dimensions: Ø6.2, Ø8.6, 4.5, 9.2, 11.5, 16, 16, R1, Ø5.2, Ø8.6, 4.3, 9.2, 11.5, 16, 16, R1, 53, 19.2

**RUBBER
HARDWARE
TAPES
SEALANTS**