

Skirting Rubber 65A - 5MPA

IRS Natural Rubber Skirting

Top grade, 65 Shore A hardness

For use along conveyor belts and conveyor systems in heavy mining applications to minimise dust, product spillage, reduce wear to the conveyor as well used in construction sites and civil engineering projects.

Supplied as full slabs or as pre-cut rubber strips all can be cut to order by our

IRS 'In House Cutting'

we can supply any project with any required cutting to design meeting any application requirements.



Name: Rubber skirting	Specs: 6.5mm-16mm
Color: Black	Test date: 2018.07.31
Test temperature: 25°C	Relative humidity: 35%
Test by: GB/T5574-1994	
Correlation criterion:GB/T528-1998 GB/T3512-1989 GB/T531-1992	
Test item	Actual result
Shore A hardness degrees	65 ± 5
Tensile strength at break	MPA 5
Elongation at break change	% 250
Specific weight	g/cm3 1.4



PART NO.	DESCRIPTION	SIZE (MM)	COLOR	TYPE
SRSKIRT6.35X200MM	NATURAL SKIRTING 6.35MM X 200MM X 5MPA	6.35MM	BLACK	NR/SBR
SRSKIRT6.35X250MM	NATURAL SKIRTING 6.35MM X 250MM X 5MPA	6.35MM	BLACK	NR/SBR
SRSKIRT12X75MM	NATURAL SKIRTING 12MM X 75MM X 5MPA	12MM	BLACK	NR/SBR
SRSKIRT12X200MM	NATURAL SKIRTING 12MM X 200MM X 5MPA	12MM	BLACK	NR/SBR
SRSKIRT12X250MM	NATURAL SKIRTING 12MM X 250MM X 5MPA	12MM	BLACK	NR/SBR
SRSKIRT12X300MM	NATURAL SKIRTING 12MM X 300MM X 5MPA	12MM	BLACK	NR/SBR



I.R.S.

Build With Quality

RUBBER
HARDWARE
TAPES
SEALANTS

1300 767 567

www.indrub.com.au