

tesa® 60402



Product Information

Hard grade PVC closed cell double sided foam tape 1.6mm thick (black). Ideal for use in the glazing market

tesa® 60402 is a 1.6mm hard grade closed cell PVC foam tape with a paper liner and an aggressive acrylic adhesive on both sides. The closed cell foam can create a waterproof barrier when compressed while still being flexible enough to seal uneven surfaces. The high-density foam has excellent resistance to water penetration, making it the ideal choice for sealing applications in the glazing market. The product is silicone compatible and available in customised die cuts. tesa® 60402 is resistant to fungi, oxidation, UV and ozone. It also complies with A.A.M.A. **810-85 type 1 and AS 2047 standards. tesa® 60402 has a permanently elastic adhesive and is not suitable for bonding or mounting applications.

Main Application

- tesa® 60402 foam tape is an approved primary glazing seal for domestic and commercial glazing systems
- The foam tape is used as a primary seal between the glass and metal frame in commercial and domestic windows and window walls
- The sealing tape is ideal for damping vibrations between the metal frame and cladding in the transport industry
- tesa® 60402 is used as a die cut corner seal in domestic and commercial windows
- The tape is available in a range of thicknesses: 1.6mm, 3.2mm, 4.8mm and 6.4mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PVC foam	• Type of adhesive	acrylic
• Color	black	• Elongation at break	160 %
• Total thickness	1600 µm	• Type of liner	paper

Properties

- Temperature resistance long term 90 °C

Additional Information

REACH and RoHS compliant

tesa® 60402

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=60402>