



I.R.S.

Build With Quality

RUBBER
HARDWARE
TAPES
SEALANTS
CUTTING

1300 767 567

www.indrub.com.au



Neoprene Foam Roll - Black 711

Durable, flexible rubber material designed for a wide range of industrial, commercial, and general-purpose applications. Manufactured from high-quality neoprene, it offers excellent resistance to weathering, moisture, and moderate chemicals, making it suitable for both indoor and outdoor use. This neoprene roll is easy to cut, shape, and install for applications such as sealing, gasketing, padding, insulation, vibration dampening, and protective linings. Ideal for workshops, maintenance teams, and fabrication environments where a reliable and versatile elastomer solution is required.

Colour	Black	Hardness	18±5 IRHD
(AC) Hardness	18±5	ASTM D2240	
Density (kg/m ³)	150±30	ASTM D3574	
Tensile Strength (MPa)	≥0.5	ASTM D412	
Elongation Rate (%)	≥150	ASTM D412	
Tearing Strength (kN/m)	≥3	ASTM D624	
Water Absorption (%)	≤5	ASTM D1056	
Compressive Strength (25% kPa)	30-65	ASTM D1056	
Compression Deflection (25% 70°C 22 hrs 30 min) (%)	≤30	ASTM D395	
High Temp Resistance (90°C 2 hrs) (%)	≤4	ASTM D1056	
Flame Retardant Rating (T≥8mm)	HBF	UL94	

AVAILABLE SIZES

STANDARD THICKNESS (MM) 1.6mm, 3.2mm, 4.8mm, 6.4mm, 9.5mm, 12.7mm and 19mm

STANDARD ROLL WIDTH (MM) 6mm, 12mm, 18mm, 24mm, 36mm and 48mm
(custom widths available)

STANDARD ROLL LENGTH (M) 7m, 15m and 25m rolls (depending on thickness)

While every effort has been made to supply accurate information, these specifications should be used as a guide only. The above datasheet is subject to Manufacturers Association Tolerances. Rubber production quantities may vary by +/- 10%.

www.indrub.com.au
1300 767 567