



## NBR + PVC SPONGE ADHESIVE TAPE 606 SERIES



Colour	Black	
(AC) Hardness	18±5	ASTM D2240
Density (kg/m <sup>3</sup> )	80±15	GB/6343-2009
Tensile Strength (MPa)	≥120	GB/6343-2009
Elongation Rate (%)	≥100	GB/6343-2009
Tearing Strength (kN/m)	≥1.2	GB/T 10808-2006
Water Absorption (%)	≤10	
Compression Deflection (25% 70°C 22 hrs 30 min) (%)	≤30	GB/T6669-2008
Shrinkage (70°C 24 hrs) (%)	≤3	JIS K6767
(13MM)	HB	UL-94 VO
2500 VDC	≤4	ASTM D419

### USES

NBR + PVC Sponge is an excellent product for uneven surfaces and sealing applications requiring a durable economically priced solution.

### AVAILABLE SIZES

**STANDARD THICKNESS (MM)** 3.2mm, 6.4mm, 9.5mm and 12.7mm

**STANDARD ROLL WIDTH (MM)** 12mm, 18mm, 24mm, 36mm and 48mm

**STANDARD ROLL LENGTH (M)** 9m roll

While every effort has been made to supply accurate information, these specifications should be used as a guide only. The above datasheet is subject to Manufacturers Association Tolerances. Rubber production quantities may vary by +/- 10%.